


Koster Pole



Koster mounted on pole 1273, further information on pages 417 - 418.

CE	220-240V	IK10	IP65	⏚	DIM	DALI
LED	E27	Al	PC	50	60	



Colour:

- Aluminium
- Graphite

Colour temperature:


2700K* 3000K 4000K



*2700K on request only, contact your supplier.



Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.




Energy under control (mainly energy-saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Luminaires sold separately, recommended poles $\varnothing 50$ and $\varnothing 60$, further information on pages 417 - 418.


Art. 7660

Adapter $\varnothing 60$ for mounting on pole $\varnothing 76$




Art. 405

Concreting anchor



Art. 406

Anchoring support





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1815AL	LED	14,4W	1991lm	3000K	> 120 000h	-	IESNA type V
1815GR			2747lm				
1823AL		19,4W	2718lm	4000K			
1823GR			2718lm				
1843AL		14,4W	2031lm	4000K			
1843GR			2031lm				
1835AL		17,5W	1625lm	3000K	50 000h	-	
1835GR			1568lm				
5070AL							
5070GR							
1915AL							
1915GR							



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1817AL	LED	14,4W	1991lm	3000K	> 120 000h	-	IESNA type V
1817GR			2747lm				
1825AL		19,4W	2718lm	4000K			
1825GR			2718lm				
1845AL		14,4W	2031lm	4000K			
1845GR			2031lm				
1837AL		17,5W	1625lm	3000K	50 000h	-	
1837GR			1568lm				
5006AL							
5006GR							
1913AL							
1913GR							



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1816AL	LED	14,4W	1991lm	3000K	> 120 000h	-	IESNA type V
1816GR			2747lm				
1824AL		19,4W	2718lm	4000K			
1824GR			2718lm				
1844AL		14,4W	2031lm	4000K			
1844GR			2031lm				
1836AL		17,5W	1625lm	3000K	50 000h	-	
1836GR			1568lm				
5007AL							
5007GR							
1914AL							
1914GR							



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class	Lens			
1155AL	E27	-	-	-	-	-					
1155GR											
1157AL	LED	35W	3136lm	3000K	> 50 000h	-	I	-			
1157GR			3250lm	4000K							
1159AL		34W	3422lm	3000K	> 120 000h	Dimmable	II				
1159GR			3624lm	4000K							
1165AL	LED	37W	3654lm	3000K				> 120 000h	DALI2/ NightDim	I	IESNA type V
1165GR			3825lm	4000K							
1167AL											
1167GR											
1173AL											
1173GR											
1175AL											
1175GR											



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class	Lens
1177AL	E27	-	-	-	-	-		
1177GR								
1179AL	LED	35W	3136lm	3000K	> 50 000h	-	I	-
1179GR			3250lm	4000K				
1181AL		34W	3422lm	3000K	> 120 000h	Dimmable	II	
1181GR			3624lm	4000K				
1187AL	3654lm		3000K					
1187GR	3825lm	4000K						
1189AL	LED	37W	3654lm	3000K	> 120 000h	DALI2/ NightDim	I	IESNA type V
1189GR			3825lm	4000K				
1195AL								
1195GR								
1197AL								
1197GR								